Serial No.: 10/017,388 Art Unit 2623

Jan-28-2005 16:17

Filed December 18, 2001

## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application.

## **Listing of Claims:**

1. (Original) An image interpolation method, comprising.

acquiring a first image pair, comprising two key frames, and first corresponding point data between the two key frames of the first image pair;

acquiring a second image pair, comprising two key frames, and second corresponding point data between the two key frames of the second image pair; and

generating an intermediate frame by interpolation, wherein the interpolation utilizes positional relations of a first axis and a second axis and the first corresponding point data and the second corresponding point data,

the first axis being determined temporally or spatially between the two key frames of the first image pair, and

the second axis being determined temporally or spatially between the two key frames of the second image pair.

2. (Original) A method according to Claim 1, wherein the first image pair and the second image pair are determined so that the first axis and the second axis do not lie Senal No.: 10/017,388

Art Unit: 2623

Filed: December 18, 2001

on a same line.

3. (Original) A method according to Claim 1, wherein one of the two key frames in the

416

first image pair and one of the two key frames in the second image pair are common,

and the interpolation utilizes positional relations based on a triangle having the first

axis and the second axis as two sides thereof.

4. (Currently Amended) A method according to Claim 1, wherein the first image pair

and any of the two key frames in the second image pair do not have any key frames in

[use] common, and the interpolation utilizes positional relations based on a

quadrilateral having the first axis and the second axis as two sides opposite to each

other.

5. (Original) A method according to Claim 4, wherein a point Pc which represents the

intermediate frame within the quadrilateral is such that the point Pc divides at a ratio

of (1-t):t a line segment between a point Q, which divides a side of the quadrilateral

connecting two points corresponding to the two key frames of the first image pair at a

ratio of s:(1-s), and a point R, which divides a side of the quadrilateral connecting two

points corresponding to the two key frames of the second image pair, where s and t

are real numbers between 0 and 1.

-3-

Serial No.: 10/017,388 Art Unit 2623

Filed December 18, 2001

6. (Original) A method according to Claim 1, further comprising: acquiring a positional relation between the intermediate frame, the two key frames of the first image pair and the two key frames of the second image pair,

416

wherein the interpolation is performed based on said positional relation.

- 7. (Original) A method according to Claim 1, wherein the two key frames of the first image pair and the two key frames of the second image pair are images photographed respectively from a same view point but at different times.
- 8. (Original) A method according to Claim 1, wherein the two key frames of the first image pair and the two key frames of the second image pair are images photographed respectively from different viewpoints.
- 9. (Original) An image interpolation method, comprising:

computing a matching between a first image pair comprised of two key frames, and detecting first corresponding point data between the two key frames of the first image pair;

computing a matching between a second image pair comprised of two key frames, and detecting second corresponding point data between the two key

Serial No.: 10/017,388

Art Unit: 2623

Filed: December 18, 2001

frames of the second image pair; and

generating an intermediate frame by interpolation, by utilizing positional

416

relations of a first axis and a second axis, the first corresponding point data and the

second corresponding point data,

wherein the first axis is determined temporally or spatially between the

two key frames of the first image pair, and

the second axis is determined temporally or spatially between the two key

frames of the second image pair.

10. (Original) A method according to Claim 9, wherein said matching is computed

pixel by pixel between the two key frames.

11. (Original) A method according to Claim 10, wherein said matching is computed

pixel by pixel based on correspondence between critical points detected through

respective two-dimensional searches on the two key frames.

12 (Original) A method according to Claim 11, wherein said computing and detecting

includes:

multiresolutionalizing the two key frames by respectively extracting the critical points;

performing a pixel-by-pixel matching computation on the two key frames, at same

-5-

Serial No.: 10/017,388

Art Unit: 2623

Filed December 18, 2001

resolution levels; and

acquiring a pixel-by-pixel correspondence relation at a finest level of resolution while

inheriting a result of a pixel-by-pixel matching computation in a different resolution

level.

13. (Original) An image interpolation apparatus, comprising:

a unit which stores a plurality of key frames;

a unit which acquires temporal or spatial position data on an intermediate

frame, in relation to the key frames; and

an intermediate frame generator which generates an intermediate frame by an

interpolation processing, based on corresponding point data for a first image pair

comprised of two key frames and a second image pair comprised of two key frames,

and the position data,

wherein the first image pair and the second image pair are determined so that

a first axis determined temporally or spatially between the two key frames of the first

image pair and a second axis determined temporally or spatially between the two key

frames of the second image pair do not lie on a same line.

14. (Original) An apparatus according to Claim 13, wherein said intermediate frame

generator generates an image A corresponding to a point Q which lies on a line

-6-

Serial No 10/017,388
Art Unit: 2623
Filed, December 18, 2001

segment connecting two points that correspond to the two key frames of the first image pair, by the interpolation processing at a ratio of s:(1-s), and then generates an image B corresponding to a point R which lies on a line segment connecting two points that correspond to the two key frames of the second image pair, by the interpolation processing at a ratio of s:(1-s), and then generates an intermediate frame by performing the interpolation processing on the image A and image B at a ratio of (1-t) t, where s and t are real numbers between 0 and 1.

- 15. (Original) An apparatus according to Claim 13, further comprising a matching processor which generates the corresponding point data.
- 16. (Original) An apparatus according to Claim 13, wherein the two key frames of the first image pair and the two key frames of the second image pair are images photographed respectively from a same viewpoint but at different times.
- 17. (Original) An apparatus according to Claim 13, wherein the two key frames of the first image pair and the two key frames of the second image pair are images photographed respectively from different viewpoints.
- 18. (Original) An apparatus according to Claim 13, further comprising a user interface

T-571 P.012/017 F-978

416

Serial No · 10/017,388

Art Unit 2623

Filed: December 18, 2001

by which to input externally a specification regarding a temporal or spatial position of the intermediate frame to be generated.

19. (Original) A method according to Claim 1, further comprising a user interface by which to input externally a specification regarding a temporal or spatial position of an intermediate frame to be generated.

20. (Original) A computer program executable by a computer, the program comprising the functions of:

acquiring a first image pair, comprising two key frames, and first corresponding point data between the two key frames of the first image pair;

acquiring a second image pair, comprising two key frames, and second corresponding point data between the two key frames of the second image pair; and

generating an intermediate frame by interpolation, wherein the interpolation utilizes positional relations of a first axis determined temporally or spatially between the two key frames of the first image pair and a second axis determined temporally or spatially between the two key frames of the second image pair, the first corresponding point data and the second corresponding point data

Serial No. 10/017,388 Art Unit 2623 Filed December 18, 2001

21. (New) A method according to claim 1, wherein said first corresponding point data and said second corresponding point data have been calculated in advance of said acquiring.